



Fuse-link, high speed, 200 A, AC 1250 V, size 1, 53 x 69 x 74 mm, aR, IEC, UL, single indicator

Catalog No. 170M4389

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	200
Rated voltage			AC 1250 V
Construction size			size 1
Size			53 x 69 x 74 mm
Utilization category			aR
Status indicator			single indicator
Description			indicator style K for microswitch
Breaking Capacity		kA	100
usable for size/applications			semiconductor protection
Standard/Approval			IEC UL
Shape			square body with flush end contacts
Standards/Regulations			IEC 60269-4

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	200
Rated voltage		V	1250
Voltage type			AC
Rated switching capacity		kA	100
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Other
Insulated metal gripping lugs (IMGL)			No

Assets (links)

Declaration of CE Conformity

00003215