



**Fuse-link, high speed, 200 A, AC 1000 V, size 1, 51 x 68 x 102 mm, aR, IEC, single indicator**

**Catalog No. 170M4532**

**Delivery program**

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	200
Rated voltage			AC 1000 V
Construction size			size 1
Size			51 x 68 x 102 mm
Utilization category			aR
Status indicator			single indicator
Description			US style indicator style K for microswitch
Breaking Capacity		kA	125
usable for size/applications			semiconductor protection
Standard/Approval			IEC
Shape			square body with centre-bolted tags
Standards/Regulations			IEC 60269-4

**Technical data ETIM 7.0**

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	200
Rated voltage		V	1000
Voltage type			AC
Rated switching capacity		kA	125
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Other
Insulated metal gripping lugs (IMGL)			No