



Fuse-link, 200 A, AC 1250 V, 100 kA, size 1, 53 x 63 x 135 mm, aR, IEC, type T indicator, live gripping lugs



Part no. **FUSE 200A 1250V 1SHT AR CU**
 Catalog No. **170M4700**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Rated current	I	A	200
Rated voltage			AC 1250 V
Construction size			size 1
Size			53 x 63 x 135 mm
Utilization category			aR
Status indicator			type T indicator
Description			live gripping lugs
Breaking Capacity		kA	100
usable for size/applications			semiconductor protection
Standard/Approval			IEC
Shape			square body with special bladed contacts
Standards/Regulations			IEC 60269-4

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	200
Rated voltage		V	1250
Voltage type			AC
Rated switching capacity		kA	100
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Top fuse status indicator
Insulated metal gripping lugs (IMGL)			No